



Spray for stencil marking

Due to their unique formulation, Elried marking sprays are suitable for permanent, highly visible marking of packaging such as wooden and cardboard boxes and metal barrels.

They are ideal for stencil markings, as the Elried marking sprays prevent a color build-up on the stencil. Due to the fast drying time, there is no annoying running of the colors behind the stencil, so that a sharp edge marking is guaranteed.

The Elried marking spray is characterized by its low inherent odor, fast drying, high opacity, weather resistance and good adhesion.

The ink is seawater resistant in accordance with DIN ISO 9227-nss and thus meets the high requirements for the marking of export goods.

**Black**

Article-No.: SS-EL-SC-00
ca. RAL 9005

**Green**

Article-No.: SS-EL-GR-00
ca. RAL 6001

**Blue**

Article-No.: SS-EL-BL-00
ca. RAL 5017

**White**

Article-No.: SS-EL-WE-00
ca. RAL 9016

**Yellow**

Article-No.: SS-EL-GE-00
ca. RAL 1018

**Red**

Article-No.: SS-EL-RO-00
ca. RAL 3020

Further Elried RAL color sprays are available on request or can be purchased in the webshop at shop.elried.de.

Technical bulletin



Application

Shake the can vigorously before each use for at least 2 minutes to ensure that the content is optimally mixed. The spray distance is 15-20 cm, depending on the application.

Spray characteristics

Spray width can be regulated by the distance to the workpiece. Very little fogging.

Storage Stability

At least 3 years if properly stored

Package size

400 ml content in 520 ml can

Packaging unit: 12 cans

Technical specifications

Resource base
Propellant
Can pressure
Colors
Temperature range

Drying time

- Acrylic resin
- Propane/Butane
- Ca. 4.2 bar
- Different, on request special colors possible
- Processing temperature 20 °C +/- 3 °C
- Still sprayable up to 3 °C, under 3 °C the spray pattern becomes worse and the stability is lost
- Ca. 5 minutes depending on layer thickness and surface



Additional guidance

The above information corresponds to our latest knowledge and many years of experience and serves the processor as an advisory aid. However, due to the variety of processing and application procedures, they are not legally binding for us and do not release the processor from checking the named products themselves for their suitability for the intended purpose. All previous product information herewith loses its validity. In addition, our terms and conditions apply in the latest version.