continuous inkjet | Ci 5300

) > elried



Excellent Value-for-Money

The Ci5300 represents the strong mid-segment within the Ci5000 series. The printer has outstanding performance features like second-to-none reliability, print quality and speed.

The Ci5300 can print 1 to 3 lines of text as well as logos and 2D barcodes in racor-sharp quality due to CiPrecisionPlus and PixelPlus technology.

Its reliability is leading in the market, proven by the unique standard warranty of 24 month, a filter with a life time of 8.000 hours and all other components, e.g. the pumps being designed for the entire life of the printer. CiSafeFill prevents operator errors and ensures a stable operation. Powered by Citronix.

Suitable for

Users who are looking for maximum availability of their printing systems and optimal readability of their prints.

Further information: www.elried.de



Wide spectrum of MEK, acetone, ethanol and special inks



1 to 3 printing lines with a character height of 1,5 - 12 mm (5 - 25 dots)



Precise 2D logos and barcodes with CiPrecisionPlus technology



Printing speed of up to 588 m/min



Maximum operational reliability, 24 months warranty







Unique, shockresistant 10" touchscreen in tablet quality



Monitoring via TCP/IP, additional RS232, USB and SD card slot

Elried Markierungssysteme GmbH | phone: +49 . 89 . 61 37 64 0 | info@elried.de | elried.de

) > elried

continuous inkjet | Ci 5300









TECHNICAL SPECIFICATIONS

	Components
Display	10.1" high-resolution and colour-intensive display with WYSIWYG print preview
	Interface with 40 languages, e.g. English, French, German, Spanish, Chinese, Russian and Japanese
	Continuous Inkjet (CII) omni-directional; for a high printing quality on nearly all surfaces and
	materials
Tank capacity	Large 1,9 liter ink tank and 2,25 liter Make-Up tank for long continuous operating times
	Precise touchscreen with keyboards for all common languages
	• Alphanumeric text and logos, date/ time, shift code, counter, lot and box number, 1D and 2D-barcodes
	• 1 to 3 line print with character height of 5 - 25 dots
Storage capacity	Over 1000 texts, logos and templates
	• Up to 588 m/min @ 50 dpi
Power supply	• AC 100 - 240 V, 50/60 Hz, 3 A, automatic switching
Printer dimension (L/W/H)	• 16" x 15,9" x 14,2" (inches) case made of powder-coaled steel
Printhead dimensions (L/W/H)	
Weight	• 18 kg (incl. print head)
Citronix ink spectrum	• MEK, ethanol and acetone black, MEK red, blue and green, alcohol resistant black, black and green
	caustic washable, acetone/ethanol black, Plastic and PlasticPlus black, UV-readabler, red and blue
	ood grade, thermochromic black to red
Features	Flexible 2,7 m printhead conduit (optional 4,6 m)
	Ci Safe Fill to prevent downtime due to mixing up ink bottles
	 SmartFlush - automatically cleans printhead at shutdown, ensuring excellent start up printing
	performance
	• Drop size can be adjusted between Normal 60 μ m and Macro 75 μ m within the software
	IP55 rating against dust and water
	Ethernet, R232, USB port and SD card slot
	Programmable password security
	Citronix PixelPlus and ciPrecisionPlus for high print quality
	Installation
Mounting	Machine and floor mounting
	 Waching Up to 50 mm
Print distance	• 0) 10 50 Hull
	Optional Accessories
Photocell	Reliable and exact placement of the print even on difficult product shapes
	Precise positioning of the print and high print quality on non-constant conveyor speeds
Alarm light	Red / yellow / green signaling of the printer status with modern LED technology
Stainless steal cabinet	High quality printer stand from stainless steel, with 4 large wheels, a storage compartment and a

High quality printer stand from stainless steel, with 4 large wheels, a storage compartment and a lockable door

Operating Environment

41 - 113 °F with 10 - 90% humidity (non-condensing)

Warranty

• 24 months (consumables excluded)

Elried Markierungssysteme GmbH | phone: +49.89.6137640 | info@elried.de | elried.de