



The best printer for rough environments

The Ci5650 is a high performance printer for rough environments: With the IP65 classification, a pressurized printer cabinet and a print head suitable for extremely dusty or wet environments, not much can stop this machine.

It also shares the unique features of the Ci5500, including 5-line print, logos and 2D codes in razor-sharp quality and a printing speed of up to 588 m/min. The reliability is market-leading, supported by the unique 30-months standard warranty.

Powered by Citronix.

Suitable for

Users valuing protection class IP65 in their production process due to above average dust accumulation and moisture.

Further information: www.elried.de



Wide spectrum of MEK, acetone, ethanol and special inks



1 to 5 printing lines with a character height of 1,5 - 12 mm (5 - 31 dots)



Precise logos and 2D barcodes with CiPrecisionPlus technology



Printing speed of up to 588 m/min



Ideal of operational reliability, 30 months warranty



IP65 water and dust protection, pressurized printing system



10" WYSIWYG display with highly intuitive user interface



Communication and monitoring via ethernet and RS232



TECHNICAL SPECIFICATIONS

Display Language Print technology	Components <ul style="list-style-type: none"> • 10.1" High-resolution display with WYSIWYG text preview • Interface with 40 languages, e.g. English, French, German, Spanish, Chinese, Russian and Japanese • Continuous Inkjet (CIJ) omni-directional; for a high printing quality on nearly all surfaces and materials
Tank capacity Input Message capabilities	<ul style="list-style-type: none"> • Big 1.9 liter ink tank and 2.25 liter Make-Up tank for long continuous operating times • Precise touchscreen with keyboards for all common languages • Alphanumeric text and logos, date/ time, shift code, counter, lot and box number, ID and 2D-barcodes
Storage capacity Line speed Power supply	<ul style="list-style-type: none"> • 1 to 5 line print with character height of 5 - 31 dots • Over 1000 texts, logos and templates • Up to 588 m/min @ 50 dpi • AC 100-240 V, 50/60 Hz, 3 A, automatic switching
Printer dimension (L/W/H) Printhead dimensions (L/W/H) Weight	<ul style="list-style-type: none"> • 16" x 15.9" x 14.2" (inches) case made of stainless steel • 10" x 1.56" x 1.56" (inches) • 1873 kg (incl. print head)
Citronix ink spectrum	<ul style="list-style-type: none"> • MEK Black, Ethanol Black, Acetone Black, MEK Red, MEK Blue, MEK Green, alcohol resistant Black, Black with washable lye, Acetone/Ethanol Black, Plastic Black, PlasticPlus Black, UV-readable, Red in food quality, Thermochromic Black to Red
Features	<ul style="list-style-type: none"> • Flexible 2.7 m printhead conduit (optional 4.6 m) • Ci Safe Fill to prevent false filling • SmartFlush - automatically cleans printhead at shutdown, ensuring excellent start up printing performance • Drop size can be changed between Normal 60 mu and Macro 75 mu within the software • IP65 rating against dust and water, pressurized printer cabinet • Ethernet, R232, USB port and SD card slot • Programmable password security • Citronix PixelPlus and ciPrecisionPlus for high print quality
Mounting Print distance	Installation <ul style="list-style-type: none"> • Machine and floor mounting • Up to 50 mm
Photocell Shaft encoder Alarm light Stainless steel cabinet	Optional accessories <ul style="list-style-type: none"> • Reliable and exact placement of the print even on difficult surfaces • Precise positioning of the print and high print quality on non-constant conveyor speeds • Red/ yellow/ green signaling of the printer status with modern LED technology • High quality printer stand from stainless steel, with 4 large wheels, a storage compartment and a lockable door
Environment	<ul style="list-style-type: none"> • 41 - 113 °F with 10 - 90% humidity (non-condensing)
Warranty	<ul style="list-style-type: none"> • 30 months (consumables excluded)